

[2017-Sep.-Updated!100% Exam Pass-300-160 Dumps VCE and PDF Free from Braindump2go[89-100]

2017/Sep New 300-160 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-160 Questions:

1.|2017 New 300-160 Exam Dumps (PDF & VCE) 403Q&As Download: <https://www.braindump2go.com/300-160.html> 2.|2017 New 300-160 Exam Questions & Answers Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNZ21HQjE0YzFwTWs?usp=sharing>

QUESTION 89 Which statement about FCoE is true? A. FCoE is not supported on any Nexus 2000 Series Fabric Extenders. B. Not a single FCoE VLAN can map to multiple VSANs. C. Inter-switch FCoE links can be configured to carry multiple VSANs. D. FCoE does not support NPV/NPIV mode. Answer: C

QUESTION 90 Which Cisco management tool provides centralized device and security policy management for Cisco VSG for Cisco Nexus 1000V Series Switches? A. Cisco UCS Manager B. Cisco NAM C. Cisco VNM D. Cisco DCNM Answer: C

QUESTION 91 Which two options are benefits of using Cisco UCS Unified Uplinks? (Choose two.) A. ability to use virtual port channels B. optimal use of bandwidth C. fewer packets drops D. consistent optics in Fabric Interconnects E. no storage license required on the Fabric Interconnects F. longer distances possible Answer: BD

QUESTION 92 You have designed a Cisco UCS Solution, and each Cisco UCS 6248UP Fabric Interconnect has these connections:- 4 x Cisco UCS Chassis each with 4 x 10 Gb links per Fabric- 4 x 10 Gb Unified Port Channel to the upstream Nexus switch How many additional Fabric Interconnect port licenses are required? A. 16 B. 0 C. 20 D. 4 E. 40 Answer: A

QUESTION 93 Which option describes how a port is configured as a unified uplink when using Cisco UCS Manager? A. configured as an FCoE uplink port B. configured as an uplink port, then as an FCoE uplink port C. configured as an FC uplink port, then as an uplink port D. configured as an FCoE storage port E. configured as an uplink port, then as an FC uplink port Answer: B

QUESTION 94 You are designing a Cisco UCS Solution that uses Cisco VIC 1280 Mezzanine Adapters. Which design decision helps prevent potential bottlenecks in the system? A. Configure a NIC team, and use per VM load balancing in vCenter. B. Use the VIC 1280 in combination with the 2208XP IO Module. C. Ensure all links between the Cisco Fabric Interconnect and IO Module are configured as a port channel. D. Utilize all links between the Cisco Fabric Interconnect and IO Module. E. Configure the vNIC for an MTU of 9000. Answer: C

QUESTION 95 The client's data center manager has requested the physical weights of the equipment in your Cisco UCS design along with the power and cooling requirements. Where in cisco.com can you find this information? A. the product datasheets B. the Cisco UCS power calculator C. the Cisco UCS GUI Configuration Guide D. the Cisco UCS Hardware Installation Guide E. the Hardware and Software Interoperability Matrix Utility Tool Answer: B

QUESTION 96 A client has five Cisco UCS domains and is looking for the most efficient method in which to manage them. Which solution best suits this need? A. Cisco UCS Director B. Data Center Network Manager C. Cisco Prime Infrastructure D. Cisco UCS Central E. Cisco Prime Network Services Controller Answer: D

QUESTION 97 Which two business requirements have the most influence on the data center design? (Choose two.) A. reduce power consumption B. increase network bandwidth C. increase storage capacity D. increase cooling requirement E. reduce virtual machine to host ratio F. reduce data center footprint (floorspace) Answer: AE

QUESTION 98 Your Cisco UCS design contains this hardware:- 2 x 6248UP Fabric Interconnects- 1 x 5108 Chassis containing a pair of 2204XP IO Modules- 8 x B200M3 blades, each with a VIC 1240 and no mezzanine adapter What is the maximum available bandwidth per fabric for each server? A. 10 Gb B. 20 Gb C. 40 Gb D. 80 Gb E. 160 Gb Answer: A

QUESTION 99 Which four options are important points within the Cisco UCS design? (Choose four.) A. preferred MAC address format B. preferred guest operating systems C. DNS configuration D. preferred WWPN format E. service profile naming conventions F. preferred backup strategy G. Cisco IMC IP addressing range H. ESX host IP addressing Answer: ADEG

QUESTION 100 Which command does a mainframe use for all subsequent logins for either virtual machines or logical partitions, after the initial connection and login process? A. F-Port login process B. N-Port ID Virtualization C. FDISC login commands D. Fibre Channel IDs Answer: C !!!RECOMMEND!!!

1.|2017 New 300-160 Exam Dumps (PDF & VCE) 403Q&As Download: <https://www.braindump2go.com/300-160.html> 2.|2017 New 300-160 Exam Questions & Answers Download: YouTube Video: [YouTube.com/watch?v=DADPr4lm2as](https://www.youtube.com/watch?v=DADPr4lm2as)