

[2018-April-NewExam Pass 100% !Braindump2go 642-887 Dumps VCE 190Q Instant Download[138-148

2018 April New Cisco 642-887 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 642-887 Real Exam Questions:1. |2018 Latest 642-887 Exam Dumps (PDF & VCE) 190Q&As
Download:<https://www.braindump2go.com/642-887.html>2. |2018 Latest 642-887 Exam Questions & Answers
Download;<https://drive.google.com/drive/folders/0B75b5xYLjSSNeXNhZVIPaDA3dDA?usp=sharing>
QUESTION 138 Refer to the exhibit. IT administrators report packet loss on the critical applications coming with CoS 4. Which option is the appropriate configuration to have a lower drop probability when the packets are processed using DSCP values? A. set ip dscp af2B. set ip dscp af4C. set ip dscp af13D. set ip dscp af32
Answer: BQUESTION 139 An engineer looks at packet captures and sees that the MPLS header field of a packet indicates a bottom of stack field of 0. What can the engineer conclude from this information? A. The packet is an AToM packetB. One label is on the packetC. At least one more MPLS label is on the packetD. No labels are on the packet
Answer: CQUESTION 140 Which option is the correct definition of the LB on a Cisco router? A. a table used by switching functions to forward labeled packetsB. a table that holds the next hop for destination prefixesC. a label-based adjacency tableD. a table that stores remote and local label bindings
Answer: AQUESTION 141 Which two values must be specified in a Cisco NBAR configuration? (Choose two.) A. port numberB. IP precedenceC. neighbor discovery addressD. CoSE. transport protocol
Answer: AEQUESTION 142 An engineer is deploying CB-WRED across the entire core network to enforce the previously deployed CBWFQ and decides to change the WRED default to make it work with DSCP. Which policy-map command enables this new profile on regular Cisco IOS routers? A. random-detectB. random-detect dscp valueC. random-detect dscp basedD. random-detect precedence value
Answer: CQUESTION 143 Which two protocols facilitate label bindings by neighboring routers? (Choose two.) A. IS-ISB. LDPC. OSPFD. EIGRPE. BGP
Answer: BEQUESTION 144 Refer to the exhibit. A network engineer who is working for an ISP wants to override the QoS that comes from the customer. The engineer wants to set a QoS value of 5 for all traffic. What are two reasons why the configuration is not working? (Choose two.) A. The service-policy command should point to the service policy, not to the class mapB. The set command should reference CoS instead of MPLS EXP bitsC. The service-policy configuration should be set as outputD. The policy-map configuration needs to reference class-map Custom1E. The number 350 in the xconnect command should appear after the encapsulation type
Answer: ADQUESTION 145 Which two values are class-selector DSCP values? (Choose two.) A. 001001B. 000111C. 111000D. 100000E. 000001
Answer: CDQUESTION 146 Which IOS XR Software feature supports establishing point-to-point and point-to-multipoint TE tunnels traversing multiple IGP areas and levels allowing headend and tailend routers to reside in different areas? A. loose hop reoptimizationB. FRR mode protectionC. interarea supportD. loose hop expansion
Answer: BQUESTION 147 Which option describes the IPv6 flow label field? A. a 3-bit field used for marking a traffic flowB. an 8-bit field used for labeling a traffic flowC. a 20-bit field used to tag a traffic flow throughout the networkD. an 8-bit field out of which the first 6 are used to classify packets
Answer: CQUESTION 148 What is a crucial LDP default operating behavior? A. LDP uses the solicited mode by default. An LDP label request is sent to the FIB next hop LSR. When the egress router receives the request, it returns message with all the label-mapping information for the LSP is generated.B. LDP establishes a TCP session between the PE routers, thus providing label mapping for the LSPC. LDP uses downstream unsolicited mode by default. An LSR advertises label mappings to peers without being askedD. LDP uses UDP-confirmed messages to establish sessions between PE ingress and egress routers. The UDP messages encode the label information for each LSP and sub-LSP link
Answer: C!!!RECOMMEND!!!1. |2018 Latest 642-887 Exam Dumps (PDF & VCE) 190Q&As Download:<https://www.braindump2go.com/642-887.html>2. |2018 Latest 642-887 Study Guide Video: YouTube Video: [YouTube.com/watch?v=LWvoUnml3Vc](https://www.youtube.com/watch?v=LWvoUnml3Vc)