

## [2018-April-NewValid Braindump2go 300-180 Exam Dumps 374Q Offer[141-151

2018 April New Cisco 300-180 Exam Dumps with PDF and VCE Free Updated Today! Following are some new CV0-001 Real Exam Questions:1.|2018 Latest 300-180 Exam Dumps (PDF & VCE) 374Q&As Download:  
<https://www.braindump2go.com/300-180.html>2.|2018 Latest 300-180 Exam Questions & Answers Download:  
<https://drive.google.com/drive/folders/0B75b5xYLjSSNRfptN0xiTENBMzA?usp=sharing>**QUESTION 141**Which command helps to determine if there are any conflicts in the network with respect to a FabricPath configuration?  
A. show licenses  
B. show fabricpath conflict  
C. show fabricpath conflict all  
D. switchport mode fabricpath  
**Answer: C****QUESTION 142**You attempt to install the 64-bit version of Windows Server 2008 on a Cisco UCS C-Series Rack-Mount Server. The installation starts, but the operating system fails to recognize the hard drive or the RAID array. Which option is the cause of the problem?  
A. Windows Server 2008 is incompatible with Cisco UCS C-Series servers.  
B. The HDD firmware is too old and fails to be recognized by the operating system.  
C. LSI drivers are not bundled in the 64-bit version of Windows 2008.  
D. Microsoft operating systems are cannot be installed on RAID arrays.  
**Answer: C****QUESTION 143**You use external storage to SAN boot Cisco UCS B-Series Blade Servers. The servers also have internal disks. You discover that one of the servers fails to boot from the SAN. Which two options do you verify? (Choose two.)  
A. the cabling  
B. the zoning  
C. the LUN masking on the storage array  
D. the boot order of the blade servers  
E. the blade power consumption  
**Answer: BC****QUESTION 144**You use dynamic vNICs. You create a new service profile. You receive an error message that indicates that you exceeded the number of dynamic vNICs. Which two components can affect the maximum number of dynamic vNICs in the Cisco UCS environment? (Choose two.)  
A. the model of the fabric interconnects  
B. the number of chassis uplinks  
C. the model of the FEXD. VMDirectPath sizing  
**Answer: AB****QUESTION 145**You discover that a new blade server encounters power spikes during peak hours. Which action occurs during the power spikes if you use manual blade-level power capping?  
A. The blade shuts down.  
B. An alert is generated.  
C. Power is reduced.  
D. The chassis enters standby mode.  
**Answer: C****QUESTION 146**Which two statements about the Cisco UCS FSM are true? (Choose two.)  
A. The FSM is run on the DME.  
B. The FSM is a workflow model with a finite number of stages.  
C. The FSM is a process to upgrade the firmware.  
D. Cisco UCS has two FSMs.  
E. The FSM is used to observe the physical, logical, and virtual components on the Cisco UCS.  
**Answer: AB****QUESTION 147**Using CLI/GUI to troubleshoot packet flow from server to the fabric, you discover that the blade server 1/7 in a Cisco UCS B-Series Blade Server is running slower than expected. You must troubleshoot the problem by using packet tracing. Which three commands can you use to identify the uplink from the Cisco UCS Fabric Interconnect to the external network of the server? (Choose three.)  
A. show pinning server-interfaces  
B. show pinning border-interface active  
C. show service-profile circuit server 1/7  
D. show fex detail  
E. show pinning border-interface  
F. show interface-fex fabric  
**Answer: ABC****QUESTION 148**On a Cisco UCS C-Series Rack-Mount Server, which state of the DIMM fault LED indicates a faulty DIMM module?  
A. OFF  
B. flashing red  
C. solid amber  
D. flashing amber  
E. flashing blue  
**Answer: C****QUESTION 149**A customer deploys a new Cisco UCS environment and is deploying new ESXi hosts. The customer fails to establish network connectivity to the KVM console. Which option is the most likely cause of the problem?  
A. wrong UUID  
B. missing user rights  
C. IP addressing overlap  
D. NIC pinning  
**Answer: C****QUESTION 150**You attempt to perform an ESXi update on a Cisco UCS C250 server, but the update does not recognize the NICs. You must perform the update as quickly as possible. Which step must you do first?  
A. Check the UCS compatibility matrix and replace the NIC with a supported one.  
B. Reconfigure the NIC ID on the LOM.  
C. Update the LOM firmware by using the Cisco Host Update Utility.  
D. Update the NIC firmware by using the Cisco Host Update Utility.  
**Answer: C****QUESTION 151**How can you set a Cisco UCS C-Series Server to export tech-support data for TAC to an external file server?  
A. CIMC to a TFTP server  
B. CIMC to an RCP server  
C. FSM to a TFTP server  
D. FSM to an RCP server  
**Answer: A****!!!RECOMMEND!!!**1.|2018 Latest 300-180 Exam Dumps (PDF & VCE) 374Q&As Download:  
<https://www.braindump2go.com/300-180.html>2.|2018 Latest 300-180 Study Guide Video: YouTube Video: [YouTube.com/watch?v=CAOPD5fGrmc](https://www.youtube.com/watch?v=CAOPD5fGrmc)