

## January/2019 Braindump2go 300-175 (PDF and VCE)Exam Dumps 353Q Free Offer[Q197-Q207

January/2019 Braindump2go 300-175 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-175 Real Exam Questions:1.|2019 Latest 300-175 Exam Dumps (PDF & VCE) 353Q&As

Download:<https://www.braindump2go.com/300-175.html>2.|2019 Latest 300-175 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNZjVxdkhhREFxblU?usp=sharing>QUESTION 197Which two statements are true concerning authorization when using RBAC in a Cisco Unified Computing System? (Choose two.)A. A locale without any organizations, allows unrestricted access to system resources in all organizations.B. When a user has both local and remote accounts, the roles defined in the remote user account override those in the local user account.C. A role contains a set of privileges which define the operations that a user is allowed to take.D. Customized roles can be configured on and downloaded from remote AAA servers.E. The logical resources, pools and policies, are grouped into roles.

Answer: ACEExplanation:  
[https://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/1-4/UCSM\\_GUI\\_Configuration\\_Guide\\_1\\_4\\_chapter9.html](https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/1-4/UCSM_GUI_Configuration_Guide_1_4_chapter9.html)User roles contain one or more privileges that define the operations allowed for the user who is assigned the role.

One exception to this rule is a locale without any organizations, which gives unrestricted access to system resources in all organizations.QUESTION 198Which actions must be taken in order to connect a NetApp FCoE storage system to a Cisco UCS system?A. Ensure that the Fibre Channel switching mode is set to Switching, and use the Fibre Channel ports on the Fabric Interconnects.B. Ensure that the Fibre Channel switching mode is set to Switching, and reconfigure the port to a FCoE Storage port.C. Ensure that the Fibre Channel switching mode is set to End-Host, and use the Ethernet ports on the Fabric interconnects.D. Ensure that the Fibre Channel switching mode is set to Switching, and use the Ethernet ports on the Fabric Interconnects.

Answer: BExplanation:  
<http://www.renar.net/?p=148&lang=en>

[https://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/release/notes/UCS\\_28313.html](https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/release/notes/UCS_28313.html)QUESTION 199Which two protocols are accepted by the Cisco UCS Manager XML API? (Choose two.)A. SMASHB. HTTPSC. HTTPD. XMTPE. SNMPAnswer: BCEExplanation: