[June-2019-NewDownload Braindump2go 640-883 Dumps 140Q Free

2019 June Braindump2go Cisco CCNP SP 642-883 SPROUTE Dumps with PDF and VCE New Updated Today! Following are some new 642-883 Exam Questions: 1. | 2019 Latest 642-883 Exam Dumps (PDF & VCE) Instant Download:https://www.braindump2go.com/640-883.html2.|2019 Latest 642-883 Exam Questions & Answers Instant Download:https://drive.google.com/drive/folders/0B75b5xYLjSSNWnOtYk0yO0k1U0U?usp=sharingNew QuestionRoutes that are received from an IBGP peer will be propagated to which other routers by default? A. to the EBGP peers only B. to the IBGP peers onlyC. to both EBGP and IBGP peersD. to no other peersAnswer: ANew QuestionWhat are two characteristics of the multihomed customers to service providers connection option? (Choose two.)A. Multihomed customers must use a private AS number.B. The traffic load can be shared for different destination networks between service providers.C. Multihomed customers must receive a full routing table from the service providers.D. The routing methodology must be capable of reacting to dynamic changes. BGP is used to achieve this flexibility.E. Multihomed customers must use a provider-assigned address space.Answer: BDNew QuestionAn engineer is using configuration blocks to build policy-based routing. All other traffic must not be affected and the policy must be applied to GigabitEthernet1/0. Which block correctly implements traffic that is destined for 10.10.10.0/24 using a next hop of 192.168.55.1?A. access-list 110 permit ip any 10.10.10.0 0.0.0.255 route-map PBR permit 10match ip address 110set next-hop 192.168.55.1interface GigabitEthernet1/0ip policy route-map PBRB. access-list 110 permit ip any 10.10.10.0 0.0.0.255 route-map PBR permit 10match ip address 110set next-hop 192.168.55.1route-map PBR permit 20interface GigabitEthernet1/0ip policy route-map PBRC. access-list 110 permit ip any 10.10.10.0 255.255.255.0 route-map PBR permit 10match ip address 110set next-hop 192.168.55.1interface GigabitEthernet1/0ip policy route-map PBRD. access-list 110 permit ip any 10.10.10.0 255.255.255.0 route-map PBR permit 10match ip address 110set next-hop 192.168.55.1 route-map PBR permit 20interface GigabitEthernet1/0ip policy route-map PBRAnswer: BNew QuestionWhich option is a mechanism that can be implemented between two eBGP peers to communicate the routes each peer needs from the other?A. ORFB. ACLC. prefix listD. route mapAnswer: ANew QuestionWhich high-availability mechanism is a detection protocol that is enabled at the interface and at the routing protocol levels? A. NSFB. SSOC. NSRD. BFDE. SDRAnswer: DExplanation: http://www.cisco.com/en/US/docs/ios/12_0s/feature/guide/fs_bfd.htmlNew QuestionWhich three statements are true about route reflectors? (Choose three.)A. If the route is learned from an EBGP peer by the route reflector, it is reflected to all IBGP and EBGP peers.B. If the route is learned from a non-client IBGP peer by the route reflector, it is reflected to all EBGP peers only.C. If the route is learned from a non-client IBGP peer by the route reflector, it is reflected to EBGP peers and clients only.D. If the route is learned from a client IBGP peer by the route reflector, it is reflected to all clients only, except the originating client.E. If the route is learned from a client IBGP peer by the route reflector, it is reflected to all EBGP peers, non-clients, and clients (except the originating client). Answer: ACENew Question Examine the following route-map configuration: route-map test permit 10 match as-path 10 set community no-export additive Which of the statements below is correct?A. Any route matched by as-path access-list 10 will not be advertised to eBGP peers.B. Any route matched by as-path access-list 10 will have its BGP community attribute stripped off.C. Any route matched by as-path access-list 10 will have its BGP community attribute stripped off when the route is propagated to eBGP peers.D. Any route matched by as-path access-list 10 will have its BGP community overwritten with the no-export community. Answer: ANew QuestionWhich three actions are prerequisites to configuring the BGP link bandwidth feature? (Choose three.)A. enable BGP synchronizationB. configure BGP multipath firstC. configure eBGP multihop on eBGP peersD. enable Cisco Express Forwarding on the routerE. enable BGP community propagation between link bandwidth advertising routers Answer: BDENew Question When monitoring the OSPF operations in the network, you notice that the OSPF process is not load balancing traffic across multiple OSPF links. Which configuration adjustment could be made to enable the OSPF process to load balance traffic across multiple OSPF links?A. Enable BFD on the OSPF interfaces and on the OSPF routing process.B. Enable NSR on the OSPF routing process.C. Enable NSF on the OSPF routing process.D. Adjust the OSPF cost on the OSPF interfaces.E. Adjust the OSPF variance parameter.F. Use the wide-style OSPF metric instead of the narrow-style OSPF metric. Answer: DNew QuestionWhen redistributing routes into OSPF, which kind of routes will be redistributed by default on Cisco IOS XR Software but will not be automatically redistributed by default on Cisco IOS Software and Cisco IOS XE Software?A. Type 1 external routesB. Type 2 external routesC. subnetted routesD. /32 host routesE. tagged static routes Answer: CExplanation: New Question Nonstop Forwarding works with the Stateful Switchover feature in Cisco IOS and IOS XR software. Which three restrictions for OSPF are true? (Choose three.)A. OSPF NSF for virtual links is not supported.B. OSPF NSF for virtual links is supported.C. OSPF NSF for sham links is not supported.D. OSPF NSF for sham links is supported.E. OSPF NSF supports NSF/SSO for IPv6 traffic only.F. OSPF NSF supports NSF/SSO for IPv4 traffic only.Answer: ACFNew QuestionWhich two OSPF network scenarios require OSPF virtual link configuration? (Choose two.)A. to connect an OSPF non-backbone area to area 0 through another non-backbone areaB. to connect an NSSA area to an external routing domain C. to connect two parts of a partitioned backbone area through a non-backbone areaD. to enable route leaking from Level 2 into Level 1E. to enable route leaking from Level 1 into Level 2F. to enable OSPF traffic engineering Answer: ACNew Question Which three potential issues can cause an OSPF adjacency to not come up? (Choose three.)A. wrong area configured on OSPF peersB. wrong authentication key configured on OSPF peersC. different OSPF instance numbers configured on OSPF peersD. different OSPF instances and VRFs configured with the command: router ospf <number1> vrf <number2>E. having the no passive-interface statement configured for the interfaces on which OSPF adjacencies are expected to formF. Layer 2 connectivity problems on the shared medium of the participating OSPF-enabled routers Answer: ABFNew QuestionA network specialist is working for a large enterprise that has a BGP-enabled multihomed core infrastructure. Recently, the ISP that provides Internet connectivity to the company had to temporarily disable one of the BGP sessions as a result of routers blackholing BGP prefixes in transit. Which option can the specialist use to avoid this incident in the future? A. filtering local prefixes outbound B. using only one router as primary BGP speakerC. permitting only local prefixes outboundD. filtering external prefixes inboundAnswer: C New QuestionRefer to the exhibit. Area 1 routers must have only a default route in their OSPF routing tables. Which configuration must be completed on XR2 to meet this requirement?A. router ospf 1address-family ipv4interface GigabitEthernet0/0/0/1area 1 stub no-summaryB. router ospf 1area 1 stub no-summaryC. router ospf 1area 1 stubinterface GigabitEthernet0/0/0/1D. router ospf 1area 1 stub no-summaryinterface GigabitEthernet0/0/0/1Answer: D!!!RECOMMEND!!!1.|2019 Latest 642-883 Exam Dumps (PDF & VCE) Instant Download:https://www.braindump2go.com/640-883.html2.|2019 Latest 642-883 Study Guide Video Instant Download: YouTube Video: YouTube.com/watch?v=KTJx81WCR60