

[November-2018 High Quality Braindump2go 300-160 VCE and 300-160 PDF Dumps 169Q Free Share[Q151-Q160]

2018/November Braindump2go 300-160 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-160

Real Exam Questions:1.|2018 Latest 300-160 Exam Dumps (PDF & VCE) 169Q&As Download:

<https://www.braindump2go.com/300-160.html>2.|2018 Latest 300-160 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNZ21HQjE0YzFwTWs?usp=sharing>QUESTION 151 Which description of an edge-core-edge SAN topology is true?A. Core switches connect to servers.B. Edge switches connect to storage devices and servers.C. Core switches connect to storage devices and servers.D. Edge switches connect to each other via ISLs. Answer:

QUESTION 152 During a presentation about Fiber Channel logins when using cisco fabric interconnect switches in switch mode you discuss FLOGI and PLOGI process. Your customer ask you to define the PLOGI process which response do you provide?A. It is a process where two N_ports discover their mutual capabilitiesB. It is a process used to establish a session between two N_portsC. It is a process where N_ports obtains FCIDD. Its process where an N_Port discovers the characteristic associated with a fabricAnswer: BQUESTION 153 Which data center virtualization option allows each partition to specify a different set of administrators and maintains its all own unique configuration and set of running software process?A. VRFB. VDCC. 100vVEMD. vPCAnswer: BQUESTION 154 What is required when configuring the second fabric interconnect in a cluster configuration?A. The IP address of the default gateway must be on the same subnet as the peer fabric interconnect.B. The system name of the second fabric interconnect must be different from the system name of the first fabric interconnect.C. The IP address of the management port must be in the same subnet as the peer fabric interconnect.D. The first and the second fabric interconnects must be able to reach the DNS. Answer: BQUESTION 155 You must connect two cisco MDS 9700 Multilayer Fabric Switches over a long-distance dark fiber connection. Which action do you take to ensure that the link between the sites is used effectively?A. Ensure that frames are marked with Co's 3 when using policy mapsB. Ensure that each switch has multiple connections to the tableC. Shut down unused ports on the fabric switches and reallocate extended BB_credits to the connected portD. Adjust the QoS settings on the fabric switches to prioritize Fiber Channel traffic over data traffic Answer: AQUESTION 156 Which three statements accurately describe end host mode on cisco UCS Fabric interconnect? (choose Three)A. The Fabric interconnect must be rebooted to enable end host modeB. Network to server unicast traffic is forward to the server only if the traffic arrived on pinned up link modeC. RPF and Deja -Vue checks apply to multicast trafficD. The uplink port are placed in rapid PVST+ edge trunk stateE. Mac address learning occurs only on the server portsF. The vtp is enabled on fabric interconnect Answer: ABEQUESTION 157 Refer to the exhibit. Your client has an existing San network includes two ISL link between two cisco MDS Core switches a client ask you design a feature the load balance the iScSI exchanges coming from the initiator over the two ISL link the design must be capable for over coming failures, which design is required? A. ECMPB. FSPF supports the load balancing without the need of any additional featuresC. Fabric PathD. OXIDAnswer: DQUESTION 158 Which two components are contained within a device package that is installed on a cisco APIC?A. A device SDKB. A device driverC. A device SpecificationD. Device scriptE. Device management software Answer: CDQUESTION 159 Your company plans to build a new data center. Which two technologies can you use for the DCI to provide layer 2 endpoint mobility? (choose two)A. ADSLB. VPLSC. DSLD. DARK FIBERE. L3 VPN Answer: BCQUESTION 160 Why should you implement an adapter placement polices to assign vnics or vHBAs to vCons?A. To function service profile templates, require a specific vHBA placement for boot from SANB. Force the vHBAs and the vNICs to appear in specific order in the operating systemC. To function vHBA updating templates require a specific VHBA placement for BOOT from SAND. To function, the FCoe storage port require a specific vHBA placement for boot from SAN Answer: A!!!RECOMMEND!!!1.|2018 Latest 300-160 Exam Dumps (PDF & VCE) 169Q&As Download:

1.|2018 Latest 300-160 Exam Dumps (PDF & VCE) 169Q&As Download:

<https://www.braindump2go.com/300-160.html>2.|2018 Latest 300-160 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=TCEGSjXJQNo](https://www.youtube.com/watch?v=TCEGSjXJQNo)