

[November-2020 High Quality Braindump2go 300-715 Dumps PDF and 300-715 Dumps VCE 300-715 103Q Free Share [Q70-Q90]

2020/November Latest Braindump2go 300-715 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-715 Real Exam Questions!

QUESTION 70 In which two ways can users and endpoints be classified for TrustSec? (Choose Two.)
A. VLAN
B. SXP
C. dynamic
D. QoS
E. SGACL
Answer: A, E

QUESTION 71 Which types of design are required in the Cisco ISE ATP program?
A. schematic and detailed
B. preliminary and final
C. high-level and low-level designs
D. top down and bottom up
Answer: C

QUESTION 72 If there is a firewall between Cisco ISE and an Active Directory external identity store, which port does not need to be open?
A. UDP/TCP 389
B. UDP 123
C. TCP 21
D. TCP 445
E. TCP 88
Answer: C

QUESTION 73 What are the three default behaviors of Cisco ISE with respect to authentication, when a user connects to a switch that is configured for 802.1X, MAB, and WebAuth? (Choose three.)
A. MAB traffic uses internal endpoints for retrieving identity.
B. Dot1X traffic uses a user-defined identity store for retrieving identity.
C. Unmatched traffic is allowed on the network.
D. Unmatched traffic is dropped because of the Reject/Reject/Drop action that is configured under Options.
E. Dot1 traffic uses internal users for retrieving identity.
Answer: A, D, E

QUESTION 74 Which statement is true?
A. A Cisco ISE Advanced license is perpetual in nature.
B. A Cisco ISE Advanced license can be installed on top of a Base and/or Wireless license.
C. A Cisco ISE Wireless license can be installed on top of a Base and/or Advanced license.
D. A Cisco ISE Advanced license can be used without any Base licenses.
Answer: B

QUESTION 75 In which scenario does Cisco ISE allocate an Advanced license?
A. guest services with dACL enforcement
B. endpoint authorization using SGA enforcement
C. dynamic device profiling
D. high availability Administrator nodes
Answer: C

QUESTION 76 Which Cisco ISE node does not support automatic failover?
A. Inline Posture node
B. Monitoring node
C. Policy Services node
D. Admin node
Answer: D

QUESTION 77 Which scenario does not support Cisco ISE guest services?
A. wired NAD with local WebAuth
B. wireless LAN controller with central WebAuth
C. wireless LAN controller with local WebAuth
D. wired NAD with central WebAuth
Answer: B

QUESTION 78 By default, which traffic does an 802.1X-enabled switch allow before authentication?
A. all traffic
B. no traffic
C. traffic permitted in the port dACL on Cisco ISE
D. traffic permitted in the default ACL on the switch
Answer: D

QUESTION 79 What does MAB leverage a MAC address for?
A. Calling-Station-ID
B. password
C. cisco-av-pair
D. username
Answer: D

QUESTION 80 Which three conditions can be used for posture checking? (Choose three.)
A. certificate
B. operating system
C. file
D. application
E. service
Answer: C, D, E

QUESTION 81 Which use case validates a change of authorization?
A. An authenticated, wired EAP-capable endpoint is discovered.
B. An endpoint profiling policy is changed for authorization policy.
C. An endpoint that is disconnected from the network is discovered.
D. Endpoints are created through device registration for the guests
Answer: B
Explanation: https://www.cisco.com/c/en/us/td/docs/security/ise/1-2/user_guide/ise_user_guide/ise_prof_pol.html

QUESTION 82 An administrator is adding a switch to a network that is running Cisco ISE and is only for IP Phones. The phones do not have the ability to auto switch port for authentication?
A. enable bypass-MAC
B. dot1x system-auth-control
C. mab
D. enable network-authentication
Answer: B

QUESTION 83 A network engineer is configuring a network device that needs to filter traffic based on security group tags using a security policy on a routed into this task?
A. cts authorization list
B. cts role-based enforcement
C. cts cache enable
D. cts role-based policy priority-static
Answer: B

QUESTION 84 An engineer is working with a distributed deployment of Cisco ISE and needs to configure various network probes to collect a set of attributes from the used to accomplish this task?
A. policy service
B. monitoring
C. pxGrid
D. primary policy administrator
Answer: B

QUESTION 85 An engineer is configuring Cisco ISE to reprofile endpoints based only on new requests of INIT-REBOOT and SELECTING message types. Which probe should be used to accomplish this task?
A. MMAP
B. DNS
C. DHCP
D. RADIUS
Answer: C

QUESTION 86 An engineer is using Cisco ISE and configuring guest services to allow wireless devices to access the network. Which action should accomplish this task?
A. Create the redirect ACL on the WLC and add it to the WLC policy.
B. Create the redirect ACL on the WLC and add it to the Cisco ISE policy.
C. Create the redirect ACL on Cisco ISE and add it to the WLC policy.
D. Create the redirect ACL on Cisco ISE and add it to the Cisco ISE Policy
Answer: B

QUESTION 87 An engineer is configuring web authentication using non-standard ports and needs the switch to redirect traffic to the correct port. Which command should be used to accomplish this task?
A. permit tcp any any eq <port number>
B. aaa group server radius proxy
C. ip http port <port number>
D. aaa group server radius
Answer: C

QUESTION 88 An administrator needs to connect ISE to Active Directory as an external authentication source and allow the proper ports through the firewall. Which two ports should be opened to accomplish this task? (Choose two.)
A. TELNET 23
B. LDAP 389
C. HTTP 80
D. HTTPS 443
E. MSRPC 445
Answer: B, E

QUESTION 89 Refer to the exhibit. A network engineers configuring the switch to accept downloadable ACLs from a Cisco ISC server. Which two commands should be run to complete the configuration? (Choose two)

Switch(config)# aaa new-model
www.Braindump2go.com
Switch(config)# aaa authorization network default group radius

A. aaa authorization auth-proxy default group radius
B. radius server vsa sand authentication
C. radius-server attribute 8 include-in-access-req
D. ip device tracking
E. dot1x system-auth-control
Answer: BC
QUESTION 90
An engineer is using the low-impact mode for a phased deployment of Cisco ISE and is trying to connect to the network prior to authentication. Which access will be denied in this?
A. HTTP
B. DNS
C. EAP
D. DHCP
Answer: A
Resources From: 1. 2020 Latest Braindump2go 300-715 Exam Dumps (PDF & VCE) Free Share: <https://www.braindump2go.com/300-715.html>
2. 2020 Latest Braindump2go 300-715 PDF and 300-715 VCE Dumps Free Share: https://drive.google.com/drive/folders/1-jcJT1SxbH3DDB-cgSq_cPEhlxMEfvFK?usp=sharing
3. 2020 Free Braindump2go 300-715 PDF Download: [https://www.braindump2go.com/free-online-pdf/300-715-PDF\(73-83\).pdf](https://www.braindump2go.com/free-online-pdf/300-715-PDF(73-83).pdf)
[https://www.braindump2go.com/free-online-pdf/300-715-PDF-Dumps\(43-61\).pdf](https://www.braindump2go.com/free-online-pdf/300-715-PDF-Dumps(43-61).pdf)
[https://www.braindump2go.com/free-online-pdf/300-715-VCE\(84-95\).pdf](https://www.braindump2go.com/free-online-pdf/300-715-VCE(84-95).pdf)
[https://www.braindump2go.com/free-online-pdf/300-715-VCE-Dumps\(62-72\).pdf](https://www.braindump2go.com/free-online-pdf/300-715-VCE-Dumps(62-72).pdf)
Free Resources from Braindump2go, We Devoted to Helping You 100% Pass All Exams!