

[Updated 300-101 Dumps Valid Braindump2go 300-101 VCE and 300-101 PDF Dumps 739Q Offer [Q666-Q676]

2018/10/22 Braindump2go 300-101 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-101 Real

Exam Questions: 1. | 2018 Latest 300-101 Exam Dumps (PDF & VCE) 739Q&As

Download: <https://www.braindump2go.com/300-101.html> | 2018 Latest 300-101 Exam Questions & Answers

Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNUlpIeEc2YV9vRDg?usp=sharing>

QUESTION 666 Which two statements about NAT in a DMVPN environment are true? (Choose two)

A. A hub router can be behind a dynamic NAT on a device.
B. Spoke routers can reside only on the public side of a NAT device.
C. Two spokes can establish session among themselves using PAT behind different NAT devices.
D. A spoke router can be represented by a static NAT on a device.
E. A hub router can use static NAT for its public IP address.
Answer: DE

QUESTION 667 Which adverse circumstance can the TTL feature prevent?

A. routing loops
B. DoS attacks
C. link saturation
D. CAM table overload
Answer: A

QUESTION 668 Which two features are provided by EIGRP for IPv6? (choose two)

A. Backbone areas
B. SPF algorithm
C. Partial updates
D. Area border router
E. Scaling
Answer: CE

QUESTION 669 Which two EIGRP metrics have nonzero K values by default? (Choose two.)

A. reliability
B. delay
C. cost
D. load
E. bandwidth
Answer: BE

QUESTION 670 Which two features does RADIUS combine? (Choose two)

A. authorization
B. authentication
C. ssh
D. accounting
E. Telnet
Answer: AB

QUESTION 671 Refer to the exhibit. You want router R1 to perform unequal-cost routing to the 172.168.10.0/24 network. What is the smallest EIGRP variance value that you can configure on R1 to achieve this result?

A. 1
B. 2
C. 3
D. 4
Answer: C

QUESTION 672 Which IP SLA operation can be used to simulate voice traffic on a network?

A. TCP connect
B. UDP-jitter
C. ICMP-echo
D. ICMP-jitter
Answer: B

QUESTION 673 Device R1 has 1 Gigabit and 10 Gigabit Ethernet interfaces, Which command do you enter so that takes full advantage of OSPF costs?

A. R1(config router)#auto-cost reference-bandwidth 10000
B. R1(config route-map)#set metric 10000000000
C. R1(config if)#ip ospf cost 10000
D. R1(config router)#auto-cost reference-bandwidth 10000000000
E. R1(config if)# ip ospf cost 1000000000
F. R1(config route-map)#set metric 10000
Answer: A

QUESTION 674 In which network environment is AAA with RADIUS most appropriate?

A. when Apple Talk Remote Access is in use
B. when NetBIOS Frame Control Protocol is in use
C. when users require access to only one device at a time
D. when you need to separate all AAA services
Answer: C

QUESTION 675 Which command sequence can you enter on a router configure Unicast Reverse Path Forwarding in loose mode?

A. Interface GigabitEthernet0/0 ip verify unicast source reachable-via loose
B. Interface GigabitEthernet0/0 ip verify unicast source reachable-via all
C. Interface GigabitEthernet0/0 ip verify unicast source reachable-via any
D. Interface GigabitEthernet0/0 ip verify unicast source reachable-via rx
Answer: C

QUESTION 676 Which SNMP model and level can provide DES encryption?

A. SNMPV2 noAuthNoPriv
B. SNMPV3 authNoPriv
C. SNMPV3 authEn
D. SNMPV3 noAuthNoPriv
Answer: C

1. | 2018 Latest 300-101 Exam Dumps (PDF & VCE) 739Q&As

Download: <https://www.braindump2go.com/300-101.html> | 2018 Latest 300-101 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=6lHfKIW8bNY](https://www.youtube.com/watch?v=6lHfKIW8bNY)